



|                                     |         |
|-------------------------------------|---------|
| Designation :                       | 30203J2 |
| Principal dimensions(mm)            |         |
| d1 :                                | 17      |
| D :                                 | 40      |
| B :                                 | 13,25   |
| Basic load ratings(KN)              |         |
| dyc(Cr) :                           | 19      |
| stc(Cor) :                          | 18,6    |
| Pu :                                | 1,83    |
| Speed ratings(rpm)                  |         |
| Speed Ratings :                     | 13000   |
| Limiting Speed :                    | 18000   |
| Weight(Kg) :                        | 0,075   |
| ISO335                              |         |
| Dimensions (ABMA) :                 | 2DB     |
| Dimensions (mm)                     |         |
| d :                                 | 17      |
| d1□ :                               | 28      |
| B :                                 | 12      |
| C :                                 | 11      |
| r1,2(min) :                         | 1       |
| r3,4(min) :                         | 1       |
| a :                                 | 10      |
| Abutment and fillet dimensions (mm) |         |
| da(max) :                           | 23      |
| db(min) :                           | 23      |
| Da(min) :                           | 34      |
| Da(max) :                           | 34      |
| Db(min) :                           | 37      |
| Ca(min) :                           | 2       |
| Cb(min) :                           | 2       |
| ra(max) :                           | 1       |
| rb(max) :                           | 1       |
| Value                               |         |
| e :                                 | 0,35    |
| Y :                                 | 1,7     |
| Yo :                                | 0,9     |