



|                                     |       |
|-------------------------------------|-------|
| Designation :                       | 32322 |
| Principal dimensions(mm)            |       |
| d1 :                                | 110   |
| D :                                 | 240   |
| B :                                 | 84,5  |
| Basic load ratings(KN)              |       |
| dyc(Cr) :                           | 627   |
| stc(Cor) :                          | 830   |
| Pu :                                | 86,5  |
| Speed ratings(rpm)                  |       |
| Speed Ratings :                     | 1900  |
| Limiting Speed :                    | 2800  |
| Weight(Kg) :                        | 17,0  |
| ISO335                              |       |
| Dimensions (ABMA) :                 | 2GD   |
| Dimensions (mm)                     |       |
| d :                                 | 110   |
| d1□ :                               | 168   |
| B :                                 | 80    |
| C :                                 | 65    |
| r1,2(min) :                         | 4     |
| r3,4(min) :                         | 3     |
| a :                                 | 55    |
| Abutment and fillet dimensions (mm) |       |
| da(max) :                           | 137   |
| db(min) :                           | 125   |
| Da(min) :                           | 198   |
| Da(max) :                           | 226   |
| Db(min) :                           | 222   |
| Ca(min) :                           | 9     |
| Cb(min) :                           | 19,5  |
| ra(max) :                           | 3     |
| rb(max) :                           | 2,5   |
| Value                               |       |
| e :                                 | 0,35  |
| Y :                                 | 1,7   |
| Yo :                                | 0,9   |