



|                                     |         |
|-------------------------------------|---------|
| Designation :                       | 32324J2 |
| Principal dimensions(mm)            |         |
| d1 :                                | 120     |
| D :                                 | 260     |
| B :                                 | 90,5    |
| Basic load ratings(KN)              |         |
| dyc(Cr) :                           | 792     |
| stc(Cor) :                          | 1120    |
| Pu :                                | 110     |
| Speed ratings(rpm)                  |         |
| Speed Ratings :                     | 1800    |
| Limiting Speed :                    | 2600    |
| Weight(Kg) :                        | 21,5    |
| ISO335                              |         |
| Dimensions (ABMA) :                 | 2GD     |
| Dimensions (mm)                     |         |
| d :                                 | 120     |
| d1□ :                               | 181     |
| B :                                 | 86      |
| C :                                 | 69      |
| r1,2(min) :                         | 4       |
| r3,4(min) :                         | 3       |
| a :                                 | 60      |
| Abutment and fillet dimensions (mm) |         |
| da(max) :                           | 148     |
| db(min) :                           | 135     |
| Da(min) :                           | 213     |
| Da(max) :                           | 245     |
| Db(min) :                           | 239     |
| Ca(min) :                           | 9       |
| Cb(min) :                           | 21,5    |
| ra(max) :                           | 3       |
| rb(max) :                           | 2,5     |
| Value                               |         |
| e :                                 | 0,35    |
| Y :                                 | 1,7     |
| Yo :                                | 0,9     |